

















LED Profil MFL | max. LED Leistung pro Meter: 48W → 1 x Flexstrip 160 oder 2 x Flexstrip 108

ALUMINIUM PROFILE & ABDECKUNGEN ALUMINIUM PROFILES & COVERS	
  <p>AP-005-005 Aluminium Profil MFL Aluminium profile MFL</p>	  <p>AB-005-100 Aluminium Abdeckung MF Aluminium cover MF</p>

PROFIL ABDECKUNGEN UND EINSCHÜBE PROFILE COVERS AND INSETS		
  <p>AB-005-001 PMMA Abdeckung MF Flach Transparent PMMA cover MF flat transparent</p>	  <p>AB-005-003 PMMA Abdeckung MF Flach Opal PMMA cover MF flat milky</p>	  <p>AB-005-006 PMMA Abdeckung MF Rund Opal PMMA cover MF round milky</p>
  <p>AB-005-009 PMMA Abdeckung MF Eckig Opal PMMA cover MF square milky</p>	<p>Transparente Abdeckung erforderlich Transparent cover necessary</p>   <p>MP-005-001 Mikroprism. Einschub MF Transparent Microprismatic Inset MF transparent</p>	<p>Transparente Abdeckung erforderlich Transparent cover necessary</p>   <p>MP-005-003 Mikroprism. Einschub MF Opal Microprismatic Inset MF milky</p>

PROFIL ENDKAPPEN PROFILE ENDCAPS		
<p>Endkappenstärke End cap thickness 2,5mm</p>  <p>EK-005-500 Profil Endkappe MFL Flach geschlossen Profile endcap MFL flat closed</p>	<p>Endkappenstärke End cap thickness 2,5mm</p>  <p>EK-005-510 Profil Endkappe MFL Rund geschlossen Profile endcap MFL round closed</p>	<p>Endkappenstärke End cap thickness 2,5mm</p>  <p>EK-005-520 Profil Endkappe MFL Eckig geschlossen Profile endcap MFL square closed</p>

1m 2m 4m SONDERLÄNGE SPECIAL LENGTH

STANDARDLÄNGE = 2M | ALLE ANDEREN LÄNGEN SIND VOM UMTAUSCH UND DER RÜCKGABE AUSGESCHLOSSEN. LÄNGEN ÜBER 2M WERDEN MITTELS SPEDITION VERSENDET UND ERFORDERN EINE MINDESTBESTELLMENGE VON 10 STK.




STANDARD LENGTH = 2M | ALL OTHER LENGTHS ARE EXCLUDED FROM EXCHANGE AND RETURN. LENGTHS OVER 2M ARE SHIPPED BY FREIGHT CARRIER AND REQUIRE A MINIMUM ORDER QUANTITY OF 10 PCS.

HINWEIS PLEASE NOTE






Kunststoff und Aluminium besitzen unterschiedliche Ausdehnungskoeffizienten, welche bei der Montage zu berücksichtigen sind. Ausgehend von 20°C verändert sich die Länge beim Aluminium um ca. 0,25mm pro Meter und beim Kunststoff um ca. 0,70mm pro Meter je 10°C Temperaturunterschied.

Plastic and aluminium have different expansion coefficients, which must be considered during assembly. Based on 20°C the length of aluminium changes approximately 0,25mm per meter and plastic approximately 0,70 mm per meter per 10°C of difference in temperature.






LED Profile MFL | max. LED power per meter: 48W → 1 x Flexstrip 160 or 2 x Flexstrip 108

PROFIL ZUBEHÖR PROFILE ACCESSORIES		
 <p>PZ-001-002 Seilabhänger 2m inkl. Deckenbefestigung Wire suspension 2m incl. ceiling fixture</p> <p>PZ-001-005 Seilabhänger 5m inkl. Deckenbefestigung Wire suspension 5m incl. ceiling fixture</p>	 <p>PZ-002-001 Seilstopper inkl. M4 Senkkopfschraube Wire stopper incl. M4 countersunk screw</p>	 <p>EK-100-002 Torx Bit TX8 für Endkappenschrauben Torx Bit TX8 for endcap screws</p>
 <p>PZ-006-001 Saugnapf 30mm Suction cup 30mm</p>		






MFL PROFIL BESTÜCKT MIT 2 X FLEXSTRIP 36 RGB MIT EINEM LED ABSTAND VON 33MM IN KOMBINATION MIT DEN UNTERSCHIEDLICHEN ABDECKUNGEN MFL PROFILE FITTED WITH 2 X FLEXSTRIP 36 RGB WITH A LED DISTANCE OF 33MM IN COMBINATION WITH THE DIFFERENT COVERS

<p>PMMA Abdeckung MF Flach Transparent 91% Transmission</p> 	<p>PMMA Abdeckung MF Flach Transp. 91% Transmission + Mikroprismatik Transp. 95% Transmission</p> 	<p>PMMA Abdeckung MF Flach Transp. 91% Transmission + Mikroprismatik Opal 93% Transmission</p> 	<p>PMMA Abdeckung MF Flach Opal 76% Transmission</p> 	<p>PMMA Abdeckung MF Eckig Opal 76% Transmission</p> 
<p>PMMA cover MF flat transparent 91% transmission</p>	<p>PMMA cover MF flat transparent 91% transmission + Microprismatic transparent 95% transmission</p>	<p>PMMA cover MF flat transparent 91% transmission + Microprismatic milky 93% transmission</p>	<p>PMMA cover MF flat milky 76% transmission</p>	<p>PMMA cover MF square milky 76% transmission</p>

MFL PROFIL BESTÜCKT MIT 2 X FLEXSTRIP 24 ODER 72 MIT EINEM LED ABSTAND VON 16,5MM IN KOMBINATION MIT DEN UNTERSCHIEDLICHEN ABDECKUNGEN MFL PROFILE FITTED WITH 2 X FLEXSTRIP 24 OR 72 WITH A LED DISTANCE OF 16,5MM IN COMBINATION WITH THE DIFFERENT COVERS

<p>PMMA Abdeckung MF Flach Transparent 91% Transmission</p> 	<p>PMMA Abdeckung MF Flach Transp. 91% Transmission + Mikroprismatik Transp. 95% Transmission</p> 	<p>PMMA Abdeckung MF Flach Transp. 91% Transmission + Mikroprismatik Opal 93% Transmission</p> 	<p>PMMA Abdeckung MF Flach Opal 76% Transmission</p> 	<p>PMMA Abdeckung MF Eckig Opal 76% Transmission</p> 
<p>PMMA cover MF flat transparent 91% transmission</p>	<p>PMMA cover MF flat transparent 91% transmission + Microprismatic transparent 95% transmission</p>	<p>PMMA cover MF flat transparent 91% transmission + Microprismatic milky 93% transmission</p>	<p>PMMA cover MF flat milky 76% transmission</p>	<p>PMMA cover MF square milky 76% transmission</p>

MFL PROFIL BESTÜCKT MIT 2 X FLEXSTRIP 48 ODER 72 DW MIT EINEM LED ABSTAND VON 8,25MM IN KOMBINATION MIT DEN UNTERSCH. ABDECKUNGEN MFL PROFILE FITTED WITH 2 X FLEXSTRIP 48 OR 72 DW WITH A LED DISTANCE OF 8,25MM IN COMBINATION WITH THE DIFFERENT COVERS

<p>PMMA Abdeckung MF Flach Transparent 91% Transmission</p> 	<p>PMMA Abdeckung MF Flach Transp. 91% Transmission + Mikroprismatik Transp. 95% Transmission</p> 	<p>PMMA Abdeckung MF Flach Transp. 91% Transmission + Mikroprismatik Opal 93% Transmission</p> 	<p>PMMA Abdeckung MF Flach Opal 76% Transmission</p> 	<p>PMMA Abdeckung MF Eckig Opal 76% Transmission</p> 
<p>PMMA cover MF flat transparent 91% transmission</p>	<p>PMMA cover MF flat transparent 91% transmission + Microprismatic transparent 95% transmission</p>	<p>PMMA cover MF flat transparent 91% transmission + Microprismatic milky 93% transmission</p>	<p>PMMA cover MF flat milky 76% transmission</p>	<p>PMMA cover MF square milky 76% transmission</p>