




LED Profil MFR | max. LED Leistung pro Meter: 55W → 3 x Flexstrip 75 (2 x direkt & 1 x indirekt)

ALUMINIUM PROFILE & ABDECKUNGEN ALUMINIUM PROFILES & COVERS	
 AP-005-001 Aluminium Profil MFR Aluminium profile MFR	 AB-005-100 Aluminium Abdeckung MF Aluminium cover MF

Ein fester Halt der Abdeckungen kann nur gewährleistet werden, wenn das Aluminiumprofil gemeinsam mit dem Aluminiumeinsatz oder dem Modul Einsatz verwendet wird.

A firm hold of the covers can only be ensured when the aluminium profile together with the aluminium inset or the module inset is used.

PROFIL ABDECKUNGEN UND EINSCHÜBE PROFILE COVERS AND INSETS			
$\eta \approx 72\%$  AB-005-001 PMMA Abdeckung MF Flach Transparent PMMA cover MF flat transparent	$\eta \approx 57\%$  AB-005-003 PMMA Abdeckung MF Flach Opal PMMA cover MF flat milky	$\eta \approx 68\%$  AB-005-006 PMMA Abdeckung MF Rund Opal PMMA cover MF round milky	
$\eta \approx 66\%$  AB-005-009 PMMA Abdeckung MF Eckig Opal PMMA cover MF square milky	Transparente Abdeckung erforderlich Transparent cover necessary $\eta \approx 61\%$  MP-005-001 Mikroprism. Einschub MF Transparent Microprismatic Inset MF transparent	Transparente Abdeckung erforderlich Transparent cover necessary $\eta \approx 58\%$  MP-005-003 Mikroprism. Einschub MF Opal Microprismatic Inset MF milky	
 AB-005-200 ABS Profil Kabelkanalabdeckung ABS profile cable channel cover			

PROFIL ENDKAPPEN PROFILE ENDCAPS		
Endkappenstärke End cap thickness 2,5mm  EK-005-100 Profil Endkappe MFR Flach geschlossen Profile endcap MFR flat closed	Endkappenstärke End cap thickness 2,5mm  EK-005-110 Profil Endkappe MFR Rund geschlossen Profile endcap MFR round closed	Endkappenstärke End cap thickness 2,5mm  EK-005-120 Profil Endkappe MFR Eckig geschlossen Profile endcap MFR square closed

1m	2m	4m	SONDER LÄNGE	SPECIAL LENGTH
----	----	----	--------------	----------------

STANDARDLÄNGE = 2M | ALLE ANDEREN LÄNGEN SIND VOM UMTAUSCH UND DER RÜCKGABE AUSGESCHLOSSEN. LÄNGEN ÜBER 2M WERDEN MITTELS SPEDITION VERSENDET UND ERFORDERN EINE MINDESTBESTELLMENGE VON 10 STK.

STANDARD LENGTH = 2M | ALL OTHER LENGTHS ARE EXCLUDED FROM EXCHANGE AND RETURN. LENGTHS OVER 2M ARE SHIPPED BY FREIGHT CARRIER AND REQUIRE A MINIMUM ORDER QUANTITY OF 10 PCS.

HINWEIS PLEASE NOTE	
Kunststoff und Aluminium besitzen unterschiedliche Ausdehnungskoeffizienten, welche bei der Montage zu berücksichtigen sind. Ausgehend von 20°C verändert sich die Länge beim Aluminium um ca. 0,25mm pro Meter und beim Kunststoff um ca. 0,70mm pro Meter je 10°C Temperaturunterschied.	Plastic and aluminium have different expansion coefficients, which must be considered during assembly. Based on 20°C the length of aluminium changes approximately 0,25mm per meter and plastic approximately 0,70 mm per meter per 10°C of difference in temperature.

LED Profile MFR | max. LED power per meter: 55W → 3 x Flexstrip 75 (2 x directly & 1 x indirectly)

VARIANTE 1: ALUMINIUM EINSATZ MIT MFR PROFIL | VARIANT 1: ALUMINIUM INSET WITH MFR PROFILE

 AP-005-000 Aluminium Einsatz MF Aluminium inset MF	 AB-005-000 MF Berührungsschutz für Aluminium Einsatz Transparent MF touch protection for aluminium inset transparent	 EK-005-000 Profil Endkappe MF Aluminium Einsatz Profile endcap MF aluminium inset
--	--	---










VARIANTE 2: MODUL EINSATZ MIT MFR PROFIL MIT KABELFÜHRUNG | VARIANT 2: MODULE INSET WITH MFR PROFILE WITH CABLE GUIDE

 AP-005-100 MF Modul Einsatz MF module inset	 AB-005-601 PMMA Berührungsschutz MF Modul Einsatz Transparent PMMA touch protection MF module inset transparent	 EK-005-001 Profil Endkappe MF Modul Einsatz Profile endcap MF module inset
als Kabelkanalabdeckung for cable canal cover  AB-005-201 ABS Modul Einsatz Kabelkanalabdeckung ABS module inset cable channel cover		

PROFIL ZUBEHÖR | PROFILE ACCESSORIES

 PZ-001-002 Seilabhänger 2m inkl. Deckenbefestigung Wire suspension 2m incl. ceiling fixture PZ-001-005 Seilabhänger 5m inkl. Deckenbefestigung Wire suspension 5m incl. ceiling fixture	 PZ-002-003 Seilstopper mit Y-Aufhängung 120mm Seil 4mm Kugeln Wire stopper with Y-suspension 120mm wire 4mm rolls	 EK-100-002 Torx Bit TX8 für Endkappenschrauben Torx Bit TX8 for endcap screws
 PZ-006-001 Saugnapf 30mm Suction cup 30mm	Für 1 Profilverbindung sind 2 Stück Verbinder notwendig For 1 profile connection 2 pieces connectors necessary  PZ-004-005 Profilverbinder MF und SL Profile connector MF and SL	Anwendungsbeispiel MFR Profil mit Innen-, und Aussenecken Profilverbinder Application example MFR profile with Inside, - and outside corner profile connectors
 PZ-004-007 Eck Profilverbinder Innen- und Kreuzecken MF und SL Corner Profile connector inside- and cross corners MF and SL	 PZ-004-008 Eck Profilverbinder Aussenecken MF und SL Corner Profile connector outside corner MF and SL	 Innenecke inside corner Aussenecke outside corner

LED Profil MFR mit Einsatz | LED Profile MFR with Inset

MFR PROFIL BESTÜCKT MIT 2 X FLEXSTRIP 36 RGB MIT EINEM LED ABSTAND VON 33MM IN KOMBINATION MIT DEN UNTERSCHIEDLICHEN ABDECKUNGEN				
MFR PROFILE FITTED WITH 2 X FLEXSTRIP 36 RGB WITH A LED DISTANCE OF 33MM IN COMBINATION WITH THE DIFFERENT COVERS				
PMMA Abdeckung MF Flach Transparent 91% Transmission	PMMA Abdeckung MF Flach Transp. 91% Transmission + Mikroprismatik Transp. 95% Transmission	PMMA Abdeckung MF Flach Transp. 91% Transmission + Mikroprismatik Opal 93% Transmission	PMMA Abdeckung MF Flach Opal 76% Transmission	PMMA Abdeckung MF Eckig Opal 76% Transmission
				
PMMA cover MF flat transparent 91% transmission	PMMA cover MF flat transparent 91% transmission + Microprismatic transparent 95% transmission	PMMA cover MF flat transparent 91% transmission + Microprismatic milky 93% transmission	PMMA cover MF flat milky 76% transmission	PMMA cover MF square milky 76% transmission
MFR PROFIL BESTÜCKT MIT 1 X FLEXSTRIP 72 MIT EINEM LED ABSTAND VON 16,5MM IN KOMBINATION MIT DEN UNTERSCHIEDLICHEN ABDECKUNGEN				
MFR PROFILE FITTED WITH 1 X FLEXSTRIP 72 WITH A LED DISTANCE OF 16.5MM IN COMBINATION WITH THE DIFFERENT COVERS				
PMMA Abdeckung MF Flach Transparent 91% Transmission	PMMA Abdeckung MF Flach Transp. 91% Transmission + Mikroprismatik Transp. 95% Transmission	PMMA Abdeckung MF Flach Transp. 91% Transmission + Mikroprismatik Opal 93% Transmission	PMMA Abdeckung MF Flach Opal 76% Transmission	PMMA Abdeckung MF Eckig Opal 76% Transmission
				
PMMA cover MF flat transparent 91% transmission	PMMA cover MF flat transparent 91% transmission + Microprismatic transparent 95% transmission	PMMA cover MF flat transparent 91% transmission + Microprismatic milky 93% transmission	PMMA cover MF flat milky 76% transmission	PMMA cover MF square milky 76% transmission
MFR PROFIL BESTÜCKT MIT 2 X FLEXSTRIP 72 MIT EINEM LED ABSTAND VON 16,5MM IN KOMBINATION MIT DEN UNTERSCHIEDLICHEN ABDECKUNGEN				
MFR PROFILE FITTED WITH 2 X FLEXSTRIP 72 WITH A LED DISTANCE OF 16.5MM IN COMBINATION WITH THE DIFFERENT COVERS				
PMMA Abdeckung MF Flach Transparent 91% Transmission	PMMA Abdeckung MF Flach Transp. 91% Transmission + Mikroprismatik Transp. 95% Transmission	PMMA Abdeckung MF Flach Transp. 91% Transmission + Mikroprismatik Opal 93% Transmission	PMMA Abdeckung MF Flach Opal 76% Transmission	PMMA Abdeckung MF Eckig Opal 76% Transmission
				
PMMA cover MF flat transparent 91% transmission	PMMA cover MF flat transparent 91% transmission + Microprismatic transparent 95% transmission	PMMA cover MF flat transparent 91% transmission + Microprismatic milky 93% transmission	PMMA cover MF flat milky 76% transmission	PMMA cover MF square milky 76% transmission
MFR PROFIL BESTÜCKT MIT 2 X FLEXSTRIP 48 ODER 72 DW MIT EINEM LED ABSTAND VON 7,15MM IN KOMBINATION MIT DEN UNTERSCH. ABDECKUNGEN				
MFR PROFILE FITTED WITH 2 X FLEXSTRIP 48 OR 72 DW WITH A LED DISTANCE OF 7.15MM IN COMBINATION WITH THE DIFFERENT COVERS				
PMMA Abdeckung MF Flach Transparent 91% Transmission	PMMA Abdeckung MF Flach Transp. 91% Transmission + Mikroprismatik Transp. 95% Transmission	PMMA Abdeckung MF Flach Transp. 91% Transmission + Mikroprismatik Opal 93% Transmission	PMMA Abdeckung MF Flach Opal 76% Transmission	PMMA Abdeckung MF Eckig Opal 76% Transmission
				
PMMA cover MF flat transparent 91% transmission	PMMA cover MF flat transparent 91% transmission + Microprismatic transparent 95% transmission	PMMA cover MF flat transparent 91% transmission + Microprismatic milky 93% transmission	PMMA cover MF flat milky 76% transmission	PMMA cover MF square milky 76% transmission
Maximal empfohlene LED Leistung: 50W/m Maximum recommended LED Power: 50W/m  Netzteile mit max. 30mm Breite und 24mm Höhe im Profil integrierbar - Aluminium Einsatz MF erforderlich! Power Supplies with max. 30mm width and 24mm height profile integrable - aluminum insert MF required!				

